

## T18RA50HSW



**Article Number:** 120-05003

**Cable Tie for AT2000, 18 lb Tensile Strength, PA66HS, Black, 50/bandolier, 500/pkg**



Download spec sheet

### Base Data

<b>Local Order Number</b>	T18RA50HSW
<b>Type</b>	T18RA50
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• The AT2000 cable tie system is designed for automatic installation on bundles up to .75" and a minimum tensile strength of 18 lbs.</li> <li>• Available in reels of 5,000 each or bandoliers of 50 each.</li> </ul>
<b>Product Description</b>	HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.
<b>Power Supply unit</b>	Electrical
<b>Tie Closure</b>	plastic pawl
<b>Short Description</b>	Cable Tie for AT2000, 18 lb Tensile Strength, PA66HS, Black, 50/bandolier, 500/pkg

### Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	18.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	80.0 N
<b>Length L (Imperial)</b>	4.0 "
<b>Length L (Metric)</b>	4.8 mm
<b>Width W (Imperial)</b>	0.1 "
<b>Width W (Metric)</b>	2.5 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.03 "
<b>Bundle Diameter Min. (Metric)</b>	0.7 mm
<b>Bundle Diameter Max. (Imperial)</b>	0.75 "
<b>Bundle Diameter Max. (Metric)</b>	20.0 mm

### Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	500

### Material and Specifications

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes

**Operating Temperature** -40°F to +257°F (-40°C to +125°C)

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes