

1. CONDUCTOR:

- 1.1 Size and Material: 10 37/26 AWG tin-plated copper wire (unilay construction).
- 1.2 O.D.: .107" nom.

2. INSULATION:

→ DUPONT TEFLON 280



- 2.1 Extruded ETFE insulation must be smooth with no swirl)
- 2.2 Wall thickness: .0245" nom. (cannot be lower than .0225")
- 2.3 Marking on the insulation:
 - 2.3.1 Legend: X-1
 - 2.3.2 Letter height (horizontal): 1/16" nom.
 - 2.3.3 Distance between each printed legend: 1 1/2" nom.
 - 2.3.4 Engraving type: line cut.
 - 2.3.5 Color: black.
 - 2.3.6 Ink type: Caloric Color (ETFE 2805)
 - 2.3.7 Note: as per sample received
- 2.4 O.D.: .156" ± .004"
- 2.5 Color: gray.

3. PERFORMANCE:

- 3.1 Voltage rating: 1000 VAC R.M.S.
- 3.2 Temperature rating: 150°C (air) / 150°C (mineral oil)

CUSTOMER APPROVAL

Sign: _____
Date: _____

 <p>1345, Blvd. Industriels, Fort-Sheep, Quebec, Canada, J2N 2J3 Phone: (506) 293-5204 Fax: (506) 293-5211 Web Site: www.harbourind.com</p>		Description: _____ Quantity: 57104 Rec: _____	
DATE: <i>Paikha</i> DATE: July 6, 2004 VERIFIED: <i>Paikha</i> DATE: July 6, 2004	SIZE: A SCALE: --- SHEET: 1 of 1	QUALIFICATION: T B D REC: ---	
Engineering Change Notice No. _____		 This specification is the property of Harbour Industries Canada Limited and may not be reproduced or copied without the written consent of Harbour Industries Canada Limited. A member of The Manning Group of companies	
UNCONTROLLED DOCUMENT A later revision of this specification may exist.			