

## T30RA3000



**Article Number: 103-00001**

**Cable Tie for AT2060, 30 lb Tensile Strength, PA66, Natural, 3000/reel**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** T30RA3000

**Type** IT30RA

**Color** Natural (NA)

**Features and Benefits**

- The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.
- Available in reels of 3,000 each or bandoliers of 30 each.

**Product Description** HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Voltage range** 27 Volt

**Short Description** Cable Tie for AT2060, 30 lb Tensile Strength, PA66, Natural, 3000/reel

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 30.0 lbs

**Minimum Tensile Strength (Metric)** 135.0 N

**Length L (Imperial)** 6.0 "

**Length L (Metric)** 152.0 mm

**Cycle Time** 1.2 seconds

**Width W (Imperial)** 0.14 "

**Width W (Metric)** 3.6 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.5 mm

**Bundle Diameter Max. (Imperial)** 1.25 "

**Bundle Diameter Max. (Metric)** 31.0 mm

**Thickness T (Imperial)** 0.05 "

**Power Supply** Electrical

**Tension Force** Adjustable

**Thickness T (Metric)** 1.2 mm

### Logistics and Packaging

**Quantity Per** reel

**Package Quantity (Imperial)** 2

**Package Quantity (Metric)** 3000  
**Carton Quantity** 6000  
**Reel Diameter (Metric)** 450 mm  
**Reel Diameter (Imperial)** 17.7 "  
**Reel Weight (Imperial)** 7 lbs  
**Reel Weight (Metric)** 3.175 kg  
**Reel Width (Imperial)** 7.197 "  
**Reel Width (Metric)** 182.8 m  
**Weight (imperial)** 3.9 lbs

---

## Material and Specifications

**Material** Polyamide 6.6 (PA66)  
**Material Shortcut** PA66  
**US MILSPEC** MS3367-5-9  
**Flammability** UL94 V2  
**Operating Temperature** -40°F to +185°F (-40°C to +85°C)  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** Yes