

T30RA30



Article Number: 103-00002

Cable Tie for AT2060, 30 lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T30RA30

Type T30RA

Color Natural (NA)

Features and Benefits

- The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.
- Available in reels of 3,000 each or bandoliers of 30 each.

Product Description HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.

Identification Plate Position none

Releasable Closure (Yes/No) No

Voltage range 27 Volt

Short Description Cable Tie for AT2060, 30 lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 30.0 lbs

Minimum Tensile Strength (Metric) 135.0 N

Length L (Imperial) 6.0 "

Length L (Metric) 152.0 mm

Cycle Time 1.2 seconds

Width W (Imperial) 0.14 "

Width W (Metric) 3.6 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.25 "

Bundle Diameter Max. (Metric) 31.0 mm

Power Supply Electrical

Tension Force Adjustable

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 600

Carton Quantity 6000

Reel Diameter (Metric) 450 mm

Reel Diameter (Imperial)	17.7 "
Reel Weight (Imperial)	7 lbs
Reel Weight (Metric)	3.175 kg
Reel Width (Metric)	182.8 m
Reel Width (Imperial)	7.197 "
Weight (imperial)	3.9 lbs

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
US MILSPEC	MS3367-5-9
Flammability	UL94 V2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes