

T30RSF0M4



Article Number: 126-00702

Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66HS, Black, 1,000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T30RSF0M4

Type T30RSF(U)

Color Black (BK)

- Features and Benefits**
- Push Mount design provides quick and easy mounting.
 - Push mount style creates low insertion and high extraction force.
 - Ties "clicks" into place upon final installation signaling installer insertion is complete.

Product Description Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66HS, Black, 1,000/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 30.0 lbs

Minimum Tensile Strength (Metric) 135 N

Length L (Imperial) 6.3 "

Length L (Metric) 161.0 mm

Width W (Imperial) 0.14 "

Width W (Metric) 3.6 mm

Height H (Imperial) 0.2 "

Height H (Metric) 5.7 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 1.3 "

Bundle Diameter Max. (Metric) 31.0 mm

Panel Thickness Max. (Imperial) 0.09 "

Panel Thickness Min. (Imperial) 0.04 "

Mounting Hole Diameter D (Imperial) 0.19 - 0.22 "

Mounting Hole Diameter D (Metric) 4.7 - 5.5 mm

Mounting Hole Diameter D Min. (Imperial) 0.19 "

Mounting Hole Diameter D Max.0.22 "

(Imperial)

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. 5.6 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 4.8 mm

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

CSA Certified No

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS compliant (Article 4 - 1) Yes

Certification/Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes