

## T50MR0M4



**Article Number:** 113-05002

**Screw Mount Tie, 50 lb 8.5" Long, Max Bundle Diameter 1.8", #10 Screw, PA66HS, Black, 1,000/pkg**



Download spec sheet

### Base Data

**Local Order Number** T50MR0M4

**Type** T50MR

**Color** Black (BK)

**Features and Benefits**

- Mount design secures firmly with any #10 Screw.
- Screw mount style creates low insertion and high extraction force.

**Product Description** Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.

**Fixation Method (FF)** fixing hole

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Screw Mount Tie, 50 lb 8.5" Long, Max Bundle Diameter 1.8", #10 Screw, PA66HS, Black, 1,000/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225 N

**Length L (Imperial)** 8.5 "

**Length L (Metric)** 215.0 mm

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.7 mm

**Height H (Imperial)** 0.22 "

**Height H (Metric)** 5.7 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.5 mm

**Bundle Diameter Max. (Imperial)** 1.8 "

**Bundle Diameter Max. (Metric)** 45.0 mm

**Mounting Hole Diameter D (Imperial)** 0.21 "

**Mounting Hole Diameter D (Metric)** 5.4 mm

**Thickness T (Imperial)** 0.05 "

**Thickness T (Metric)** 1.2 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 1000

**Carton Quantity** 5000

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**CSA Certified** No

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS compliant (Article 4 - 1)** Yes

**Certification/Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes