

111-85871

Article Number: 111-85871

Description: 2-Piece Cable Tie/Fir Tree Mount, 8.0"L, .26"-.28" Mounting Hole Diameter, PA66HS, Black, 500/pkg



Base Data	Local Order Number	111-85871
	Type	T50RFT7
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • Staggered fir tree branch design provides low insertion forces and high extraction force. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications.
	Quantity Per	bag
	Product Description	HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.
	Short Description	2-Piece Cable Tie/Fir Tree Mount, 8.0"L, .26"-.28" Mounting Hole Diameter, PA66HS, Black, 500/pkg
Product Dimensions	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	225N
	Length L (Imperial)	7.87"
	Length L (Metric)	200mm
	Length L2 (Imperial)	0.46"
	Length L3 (imperial)	0.75"
	Length L3 (metric)	19mm
	Fixation Method	Fir Tree
	Identification Plate Position	none
	Length L2 (Metric)	11.6mm
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Inside Serrated

111-85871



Product Dimensions	Width W (Imperial)	0.18"
	Width W (Metric)	4.6mm
	Width W2 (Imperial)	0.45"
	Width W2 (Metric)	11.6mm
	Width W3 (Imperial)	0.2"
	Width W3 (Metric)	5.0mm
	Height H (Imperial)	0.05"
	Height H (Metric)	1.2mm
	Height H2 (Imperial)	0.5"
	Height H2 (Metric)	12.7mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	4.0mm
	Bundle Diameter Max. (Imperial)	2.0"
	Bundle Diameter Max. (Metric)	44.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.28"
	Panel Thickness Max. (Metric)	7.0mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.8mm
	Mounting Hole Diameter D (Imperial)	0.26 - 0.28"
	Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.256"
	Mounting Hole Diameter D Max. (Imperial)	0.276"
Thickness T (Imperial)	0.05"	
Thickness T (Metric)	1.2mm	
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes

111-85871



Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	2.3kg