

# Multi-Conductor Unshielded Cable

## Audio Control Cable UL CM, CSA AWM CMG

**Conductors:** Stranded Tin-Plated Copper  
**Insulation:** SR-PVC  
**Jacket:** Gray PVC  
**Construction:** Conductors Cabled  
**Temperature Rating:** UL 80°C (UL 60°C under 30 mil jacket thickness), CSA 105°C  
**Operating Voltage:** 300 Volts UL, 600 Volts CSA  
**Applications:** For point to point wiring of computers, control systems, electronic apparatus and panels.  
**Approvals:** UL, CM  
 CSA AWM II A/B, CMG FT4



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Color Chart	Weight Lbs/1000'
T5430	2	20	7	.010	.015	.146	Blk/Red	14
T5431	3	20	7	.010	.015	.154	1	18
T5432	4	20	7	.010	.023	.189	1	30
T5433	5	20	7	.010	.023	.197	1	34
T5435	7	20	7	.010	.023	.225	1	46
T5437	9	20	7	.010	.023	.249	1	57
T5439	12	20	7	.010	.023	.279	1	71
T5440	15	20	7	.010	.030	.306	2	93
T5441	19	20	7	.010	.030	.338	2	114
T5442	25	20	7	.010	.030	.380	2	145
T5452	2	18	16	.012	.020	.195	Blk/Red	26
T3602	2	18	16	.012	.020	.195	1	26
T5453	3	18	16	.012	.023	.207	1	34
T5454	4	18	16	.012	.023	.226	1	35
T5455	5	18	16	.012	.023	.237	1	51
T5456	6	18	16	.012	.023	.255	1	59
T5457	7	18	16	.012	.023	.271	1	67
T5458	8	18	16	.012	.023	.286	1	75
T5459	9	18	16	.012	.023	.300	1	83
T5460	10	18	16	.012	.030	.330	1	91
T5461	12	18	16	.012	.030	.353	2	110
T5462	15	18	16	.012	.030	.386	2	134
T5463	19	18	16	.012	.030	.429	2	167
T5464	25	18	16	.012	.035	.485	2	209
T5465	30	18	16	.012	.035	.524	2	247
T5466	40	18	16	.012	.050	.633	2	350

# Multi-Conductor Unshielded Cable

## Audio Control Cable UL CM, CSA AWM CMG

**Conductors:** Stranded Tin-Plated Copper  
**Insulation:** SR-PVC  
**Jacket:** Gray PVC  
**Construction:** Conductors Cabled  
**Temperature Rating:** UL 80°C (UL 60°C under 30 mil jacket thickness), CSA 105°C  
**Operating Voltage:** 300 Volts UL, 600 Volts CSA  
**Applications:** For point to point wiring of computers, control systems, electronic apparatus and panels.  
**Approvals:** UL CM  
 CSA AWM II A/B, CMG FT4



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Color Chart	Weight Lbs/1000'
T5480	2	16	26	.015	.023	.226	2	34
T5481	3	16	26	.015	.023	.240	2	46
T5482	4	16	26	.015	.023	.263	2	58
T5483	5	16	26	.015	.023	.277	2	77
T5485	7	16	26	.015	.030	.343	2	103
T5486	8	16	26	.015	.030	.353	2	112
T5487	9	16	26	.015	.030	.380	2	130
T5489	12	16	26	.015	.030	.430	2	168
T5490	15	16	26	.015	.035	.473	2	202
T5491	19	16	26	.015	.035	.524	2	250
T5492	25	16	26	.015	.050	.633	2	351
T5252	2	14	41	.030	.030	.336	2	65
T5253	3	14	41	.030	.030	.357	2	85
T5254	4	14	41	.030	.030	.392	2	108
T5255	5	14	41	.030	.030	.415	2	134
T5257	7	14	41	.030	.030	.470	2	167
T5258	8	14	41	.030	.030	.507	2	210
T5259	9	14	41	.030	.030	.534	2	232
T5262	12	14	41	.030	.050	.637	2	299
T5265	15	14	41	.030	.050	.701	2	369