

# Multi-Conductor Shielded Cable

## Audio Control Cable UL CM CSA AWM CMG

**Conductors:** Stranded Tin-Plated Copper  
**Insulation:** PVC  
**Shield:** Aluminum/Polyester Foil Shield with Tinned Copper Drain Wire  
**Jacket:** Premium Grade PVC  
**Construction:** Conductors Cabled.  
**Temperature Rating:** UL 80°C, CSA 105°C  
**Operating Voltage:** CSA 600 Volts, UL 300 Volts  
**Applications:** For point to point wiring of computers, control systems, electronic apparatus and panels where shielding is required.  
**Approvals:** UL CM CSA AWM CMG FT4



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Color Chart	Weight Lbs/1000'
T5575	2	16	26	.015	.023	.236	Blk/Red	45
T5576	3	16	26	.015	.023	.250	1	55
T5577	4	16	26	.015	.023	.274	1	62
T5578	5	16	26	.015	.023	.288	2	76
T5580	7	16	26	.015	.030	.345	2	110
T5582	9	16	26	.015	.030	.380	2	134
T5584	12	16	26	.015	.030	.432	2	173
T5585	15	16	26	.015	.035	.475	2	209
T5586	19	16	26	.015	.035	.526	2	257
T5587	25	16	26	.015	.050	.635	2	356
T8202	2	14	41	.030	.030	.338	6	73
T8203	3	14	41	.030	.030	.353	2	88
T8204	4	14	41	.030	.030	.405	2	115
T8205	5	14	41	.030	.030	.460	2	140
T8207	7	14	41	.030	.035	.480	2	183
T8209	9	14	41	.030	.035	.536	2	253
T8212	12	14	41	.030	.050	.649	2	310
T8215	15	14	41	.030	.050	.713	2	380