HellermannTyton

TAG11T4-250	
	Article Number: 596-11250
	Thermal Transfer Label, .65" X .2", 4 Across, Cloth, White, 5000/RL
HellermannTyton	Y ROHS
Download drawing	pad spec sheet
Base Data	
Local Order Numb	er TAG11T4-250
Тур	be TAG11T4
Col	or White (WH)
Features and Benef	
	 Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating th need to be dedicated to one printer model.
	• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
Product Description	n Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and
	abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The produ
	is supplied on rolls on a 3" cardboard core.
Short Description	n Thermal Transfer Label, .65" X.2", 4 Across, Cloth, White, 5000/RL
Product Dimensions	
Width W (Imperia	I) 0.65 "
Width W (Metri	c) 16.5 mm
Height H (Imperia	l) 0.20 "
Height H (Metri	c) 5.08 mm
Horizontal Repeat HR (imperia	I) 0.65 "
Horizontal Repeat HR (metri	c) 16.5 mm
Print Metho	od Thermal Transfer
Vertical Repeat VR (metri	c) 7.62 mm
Vertical Repeat VR (imperia	I) 0.30 "
Width of Liner WL (imperia	al) 2.60 "
Width of Liner WL (metri	c) 66.04 mm
Logistics and Packaging	
Quantity P	er reel

Quantity Per	reel
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Carton Quantity	5000 Pieces
Labels per Row	4

Material and Specifications

Material Shortcut	250
Adhesive Operating Temperature	-40°F to +248°F (-40°C to +120°C)
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
ROHS compliant (Article 4 - 1)	Yes

© HellermannTyton 2015