

Article Number: 594-13789

Laser Tag Label, .75" X .25", 312 Per Sheet, Polyester, White, 5000/pkg



Download spec sheet

### Base Data

**Local Order Number** TAG13L-789

**Type** TAG13L

**Color** White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
  - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
  - LaserTags are printable using toner for long term UV exposure.
  - LaserTags come in a variety of label sizes and types to fit most applications.

**Color Marking Field** White (WH)

**Product Description** LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

**Paper Format** Letter

**Short Description** Laser Tag Label, .75" X .25", 312 Per Sheet, Polyester, White, 5000/pkg

### Product Dimensions

**Length L (Imperial)** 0.25 "

**Length L (Metric)** 6.35 mm

**Width W (Imperial)** 0.75 "

**Width W (Metric)** 19.05 mm

**Height H (Imperial)** 0.25 "

**Height H (Metric)** 6.35 mm

**Height of printable area (metric)** 6.35 mm

**Horizontal Repeat HR (metric)** 24.30 mm

**Horizontal Repeat HR (imperial)** .963 "

**Print Method** Laser

**Thickness T (Metric)** 64.0 µm

**Thickness of Foil (TF)** 64 µm

**Vertical Repeat VR (imperial)** 0.25 "

**Vertical Repeat VR (metric)** 6.35 mm

**Width of Liner WL (imperial)** 8.5 "

**Width of Liner WL (metric)** 215.00 mm

### Logistics and Packaging

<b>Quantity Per</b>	pack
<b>Package Quantity (Imperial)</b>	5000
<b>Package Quantity (Metric)</b>	5000
<b>Carton Quantity</b>	5000 Pieces
<b>Labels per Column</b>	39
<b>Labels per Row</b>	8
<b>Labels per Sheet</b>	312
<b>Sheets per Pack</b>	17

---

## Material and Specifications

---

<b>Material</b>	Type 789, Polyethylenterephthalat (PET)
<b>Material Shortcut</b>	789
<b>Adhesive</b>	Acrylic
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>ROHS compliant (Article 4 - 1)</b>	Yes