

TAG15L-789

Article Number: 594-15789

Laser Tag Label, 1.0" X .50", 133 Per Sheet, Polyester, White 5000/pkg



Download spec sheet

Base Data

Local Order Number TAG15L-789

Type TAG15L

Color White (WH)

Features and Benefits

- LaserTags are sheet fed for easy loading and fast printing.
- LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
- LaserTags are printable using toner for long term UV exposure.
- LaserTags come in a variety of label sizes and types to fit most applications.

Product Description LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

Paper Format Letter

Short Description Laser Tag Label, 1.0" X .50", 133 Per Sheet, Polyester, White 5000/pkg

Product Dimensions

Length L (Imperial) 0.50 "

Length L (Metric) 12.7 mm

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Height H (Imperial) 0.50 "

Height H (Metric) 12.7 mm

Height of printable area (metric) 12.7 mm

Horizontal Repeat HR (imperial) 1.120 "

Horizontal Repeat HR (metric) 28.44 mm

Print Method Laser

Thickness T (Metric) 64.0 µm

Thickness of Foil (TF) 64 µm

Vertical Repeat VR (metric) 12.70 mm

Vertical Repeat VR (imperial) 0.5 "

Logistics and Packaging

Quantity Per pack

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

Carton Quantity	5000 Pieces
Labels per Column	19
Labels per Row	7
Labels per Sheet	133
Sheets per Pack	38

Material and Specifications

Material	Type 789, Polyethylenterephthalat (PET)
Material Shortcut	789
Adhesive Shortcut	Acrylic
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
ROHS compliant (Article 4 - 1)	Yes