

## TAG16-400

Article Number: 595-16400

Dot Matrix Label, .90" X .25", 8 Across, Polyester, White, 5000/pkg



Download spec sheet

### Base Data

**Local Order Number** TAG16-400

**Type** TAG16

**Color** White (WH)

**Features and Benefits**

- Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing.
- Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.

**Product Description** Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.

**Short Description** Dot Matrix Label, .90" X .25", 8 Across, Polyester, White, 5000/pkg

### Product Dimensions

**Length L (Imperial)** 0.25 "

**Length L (Metric)** 6.4 mm

**Width W (Imperial)** 0.9 "

**Width W (Metric)** 22.8 mm

**Height H (Imperial)** 0.25 "

**Height H (Metric)** 6.35 mm

**Height of printable area (metric)** 6.40 mm

**Horizontal Repeat HR (imperial)** 1.000 "

**Horizontal Repeat HR (metric)** 25.40 mm

**Print Method** Dot-Matrix

**Vertical Repeat VR (imperial)** 0.333 "

**Vertical Repeat VR (metric)** 8.45 mm

**Width of Liner WL (imperial)** 8.9 "

**Width of Liner WL (metric)** 226.00 mm

### Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 5000

**Package Quantity (Metric)** 5000

**Carton Quantity** 5000 Pieces

**Labels per Row** 8

**Weight (Metric)** 0.09 kg

## Material and Specifications

---

<b>Material</b>	Type 400, Polyester, white (WH)
<b>Material Shortcut</b>	400
<b>Adhesive</b>	Acrylic
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-Recognized