

Article Number: 596-00007

Thermal Transfer Self-Laminating Label, 1.0" X .5" X 1.43", 3 Across, Vinyl, White, 5000/RL



Download spec sheet

### Base Data

<b>Local Order Number</b>	TAG22T3-100B
<b>Type</b>	TAG22T3
<b>Color</b>	White (WH)
<b>Features and Benefits</b>	<ul style="list-style-type: none"><li>• HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy.</li><li>• Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.</li><li>• Labels are UL recognized for indoor and outdoor use to expand application options.</li><li>• HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.</li></ul>
<b>Color Marking Field</b>	White (WH)
<b>Product Description</b>	HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.
<b>For Wire Type</b>	4 Pair UTP / RG6 & RG59 Coax
<b>Short Description</b>	Thermal Transfer Self-Laminating Label, 1.0" X .5" X 1.43", 3 Across, Vinyl, White, 5000/RL

### Product Dimensions

<b>Length L (Imperial)</b>	1.43 "
<b>Length L (Metric)</b>	36.3 mm
<b>Width W (Imperial)</b>	1.0 "
<b>Width W (Metric)</b>	25.4 mm
<b>Height H (Imperial)</b>	1.43 "
<b>Height H (Metric)</b>	36.3 mm
<b>Height H2 (Imperial)</b>	1.43 "
<b>Height H2 (Metric)</b>	36.5 mm
<b>Height of printable area (metric)</b>	12.7 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.137 "
<b>Bundle Diameter Min. (Metric)</b>	3.5 mm
<b>Bundle Diameter Max. (Imperial)</b>	0.29 "
<b>Bundle Diameter Max. (Metric)</b>	7.6 mm
<b>Horizontal Repeat HR (metric)</b>	27.3 mm
<b>Horizontal Repeat HR (imperial)</b>	1.075 "
<b>Print Method</b>	Thermal Transfer

**Thickness T (Metric)** 25 µm  
**Vertical Repeat VR (metric)** 41.28 mm  
**Vertical Repeat VR (imperial)** 1.62 "  
**Width of Liner WL (metric)** 85.09 mm  
**Width of Liner WL (imperial)** 3.35 "

## Logistics and Packaging

---

**Quantity Per** reel  
**Package Quantity (Imperial)** 5000  
**Package Quantity (Metric)** 5000  
**Labels per Row** 3

## Material and Specifications

---

**Material** Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating  
**Material Shortcut** 100B  
**Adhesive** Acrylic  
**Adhesive Shortcut** Acrylic  
**Adhesive Operating Temperature** -40°F to +194°F (-40°C to +90°C)  
**Operating Temperature** -40°F to +194°F (-40°C to +90°C)  
**ROHS compliant (Article 4 - 1)** Yes  
**Certification/Specification** UL-Recognized