

TAG24T1-100B

Article Number: 596-00008

Thermal Transfer Self-Laminating Label, 2.0" X .5" X 1.43", 1 Across, Vinyl, White, 1000/RL



Download spec sheet

Base Data

Local Order Number TAG24T1-100B

Type TAG24T1

Color White (WH)

- Features and Benefits**
- Clear laminate provides excellent abrasion protection and chemical resistance.
 - Flexible material bends around small gauge wires and tight bends.
 - Labels are UL recognized and include a strong acrylic adhesive for indoor and outdoor use.
 - Standard 3" core can be used with HellermannTyton thermal transfer printers or most standard brands.

Product Description HellermannTyton self-laminating thermal transfer printer labels are made of a flexible vinyl film with a white printable surface that easily conforms to wires. These labels include a clear "tail" that laminates printed text when applied. Labels are UL recognized for indoor and outdoor use and feature a strong acrylic adhesive designed to bond to both large and small diameter wires.

Short Description Thermal Transfer Self-Laminating Label, 2.0" X .5" X 1.43", 1 Across, Vinyl, White, 1000/RL

Product Dimensions

Length L (Imperial) 1.43 "

Length L (Metric) 36.49 mm

Width W (Imperial) 2.0 "

Width W (Metric) 50.8 mm

Height H (Imperial) 1.43 "

Height H (Metric) 36.49 mm

Height H2 (Imperial) 1.43 "

Height H2 (Metric) 36.5 mm

Height of printable area (metric) 12.7 mm

Bundle Diameter Min. (Imperial) 0.137 "

Bundle Diameter Min. (Metric) 3.5 mm

Bundle Diameter Max. (Imperial) 0.29 "

Bundle Diameter Max. (Metric) 7.6 mm

Horizontal Repeat HR (metric) 50.8 mm

Horizontal Repeat HR (imperial) 2.0 "

Print Method Thermal Transfer

Thickness T (Metric) 25 µm

Vertical Repeat VR (imperial) 1.68 "

Vertical Repeat VR (metric) 42.6 mm

Width of Liner WL (metric) 55.9 mm

Width of Liner WL (imperial) 2.20 "

Logistics and Packaging

Quantity Per reel
Package Quantity (Imperial) 1000
Package Quantity (Metric) 1000
Labels per Column 1
Labels per Row 1

Material and Specifications

Material Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
Material Shortcut 100B
Adhesive Shortcut Acrylic
Adhesive Acrylic
Adhesive Operating Temperature -40°F to +194°F (-40°C to +90°C)
Operating Temperature -40°F to +194°F (-40°C to +90°C)
ROHS compliant (Article 4 - 1) Yes
Certification/Specification UL-Recognized