

## TAG2T5-100B

Article Number: 596-00010

Thermal Transfer Self-Laminating Label, .5" X .5" X 1.43", 5 Across, Vinyl, White, 10000/RL



Download drawing



Download spec sheet

### Base Data

**Local Order Number** TAG2T5-100B

**Type** TAG2T5

**Color** White (WH)

**Features and Benefits**

- HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy.
- Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
- Labels are UL recognized for indoor and outdoor use to expand application options.
- HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.

**Color Marking Field** White (WH)

**Product Description** HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.

**For Wire Type** 4 Pair UTP / RG6 & RG59 Coax

**Short Description** Thermal Transfer Self-Laminating Label, .5" X .5" X 1.43", 5 Across, Vinyl, White, 10000/RL

### Product Dimensions

**Length L (Imperial)** 1.43 "

**Length L (Metric)** 36.3 mm

**Width W (Imperial)** 0.5 "

**Width W (Metric)** 12.7 mm

**Height H (Imperial)** 1.43 "

**Height H (Metric)** 36.3 mm

**Height H2 (Imperial)** 1.43 "

**Height H2 (Metric)** 36.5 mm

**Height of printable area (metric)** 12.7 mm

**Bundle Diameter Min. (Imperial)** 0.137 "

**Bundle Diameter Min. (Metric)** 3.5 mm

**Bundle Diameter Max. (Imperial)** 0.29 "

**Bundle Diameter Max. (Metric)** 7.6 mm

**Horizontal Repeat HR (imperial)** 0.66 "

**Horizontal Repeat HR (metric)** 16.81 mm

**Print Method** Thermal Transfer

<b>Thickness T (Metric)</b>	25 µm
<b>Vertical Repeat VR (imperial)</b>	1.62 "
<b>Vertical Repeat VR (metric)</b>	41.28 mm
<b>Width of Liner WL (imperial)</b>	3.35 "
<b>Width of Liner WL (metric)</b>	85.09 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	reel
<b>Package Quantity (Imperial)</b>	10000
<b>Package Quantity (Metric)</b>	10000
<b>Carton Quantity</b>	10000
<b>Labels per Row</b>	5
<b>Weight (Metric)</b>	0.1 kg

## Material and Specifications

---

<b>Material</b>	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
<b>Material Shortcut</b>	100B
<b>Adhesive</b>	Acrylic
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>ROHS compliant (Article 4 - 1)</b>	Yes
<b>Certification/Specification</b>	UL-Recognized