

## Specification Sheet

Part Number: TAG2T5-100B

Product Image

**Article Number**

596-00010

**Type**

TAG2T5

**Color**

White (WH)

**Features & Benefits**

- HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy.
- Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
- Labels are UL recognized for indoor and outdoor use to expand application options.
- HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.

**Quantity Per**

roll

**Product Description**

HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.

**Short Description**

Thermal Transfer Labels, Self-Laminating, .5" x .5" x 1.43", 5 Across, VL, White, 10,000/roll

**Global Part Name**

TAG2T5-100B-WH

**Width W (Imperial)**

0.5

**Width W (Metric)** 12.7

**Bundle Diameter Min (Imperial)** .94

**Bundle Diameter Min (Metric)** 24.00

**Bundle Diameter Max (Imperial)** 0.29

**Bundle Diameter Max (Metric)** 7.37

**Thickness T (Metric)** 25

**Width of Liner (Metric)** 85.09

**Width of Liner (imperial)** 3.35

**Material** Type 100B

**Material Shortcut** 100B

**Adhesive** Acrylic

**Halogen free** No

**Adhesive Operating Temperature** -51°F to +200°F (-46°C to +93°C)

**Operating Temperature (Metric)** -40°F to +194°F (-40°C to +90°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

<b>Certification/Specification WEB</b>	UL-Recognized
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	10000
<b>Package Quantity (Metric)</b>	10000
<b>Customs Number</b>	3919102055
<b>Labels per Column</b>	1
<b>Labels per Row</b>	5
<b>Weight (Metric)</b>	1.176
<b>Weight (Imperial)</b>	2.57