HellermannTyton

TAG33T1-DTH

Article Number: 596-00039

Thermal Transfer Label, 3.0" X 2.0", 1 Across, DTH, White, 1000/RL

✔ RoHS

HellermannTyton

📄 Download drawing   📄 Download spec sheet

Base Data

Local Order Number	TAG33T1-DTH
Type	TAG33T1
Color	White (WH)
Features and Benefits	• Thermal transfer labels are made with high performance materials for long term industrial applications. • Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model. • The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
Product Description	Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.
Short Description	Thermal Transfer Label, 3.0" X 2.0", 1 Across, DTH, White, 1000/RL

Product Dimensions

Width W (Imperial)	3.0 "
Width W (Metric)	76.2 mm
Height H (Imperial)	2.0 "
Height H (Metric)	50.8 mm
Horizontal Repeat HR (imperial)	2.0 "
Horizontal Repeat HR (metric)	50.8 mm
Print Method	Thermal Transfer
Vertical Repeat VR (metric)	53.97 mm
Vertical Repeat VR (imperial)	2.125 "
Width of Liner WL (metric)	78.74 mm
Width of Liner WL (imperial)	3.10 "

Logistics and Packaging

Quantity Per	reel
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Labels per Row	1

Material and Specifications

Material	Type DTH, Durattach white (WH)
Material Shortcut	DTH

Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +140°F (-40°C to +60°C)
Operating Temperature	-40°F to +140°F (-40°C to +60°C)
ROHS compliant (Article 4 - 1)	Yes