

## TAG51L-105

Article Number: 594-51105

Laser Tag Self-Laminating Label, 1.0" X .35" X .75", 84 Per Sheet, Polyester, White, 5000/pkg



Download spec sheet

### Base Data

**Local Order Number** TAG51L-105

**Type** TAG51L

**Color** White (WH)

**Features and Benefits**

- LaserTags are sheet fed for easy loading and fast printing.
- LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
- LaserTags are printable using toner for long term UV exposure.
- LaserTags come in a variety of label sizes and types to fit most applications.

**Color Marking Field** White (WH)

**Product Description** LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

**For Wire Type** 2 Pair Fiber

**Paper Format** Letter

**Short Description** Laser Tag Self-Laminating Label, 1.0" X .35" X .75", 84 Per Sheet, Polyester, White, 5000/pkg

### Product Dimensions

**Length L (Imperial)** 0.75 "

**Length L (Metric)** 19.05 mm

**Core diameter from / to** 1.6 - 3.30 mm

**Width W (Imperial)** 1.0 "

**Width W (Metric)** 25.4 mm

**Height H (Imperial)** 0.35 "

**Height H (Metric)** 8.89 mm

**Height H2 (Imperial)** 0.75 "

**Height H2 (Metric)** 19.05 mm

**Height of printable area (metric)** 8.89 mm

**Bundle Diameter Min. (Imperial)** 0.063 "

**Bundle Diameter Min. (Metric)** 1.60 mm

**Bundle Diameter Max. (Imperial)** 0.129 "

**Bundle Diameter Max. (Metric)** 3.30 mm

**Outside Diameter Min. (Imperial)** 0.059 "

**Outside Diameter Min. (Metric)** 1.6 mm

**Outside Diameter Max. (Imperial)** 0.129 "

<b>Outside Diameter Max. (Metric)</b>	3.30 mm
<b>Horizontal Repeat HR (imperial)</b>	1.000 "
<b>Horizontal Repeat HR (metric)</b>	25.40 mm
<b>Print Method</b>	Laser
<b>Thickness T (Metric)</b>	35.0 µm
<b>Vertical Repeat VR (imperial)</b>	0.75 "
<b>Vertical Repeat VR (metric)</b>	19.00 mm
<b>Width of Liner WL (imperial)</b>	8.5 "
<b>Width of Liner WL (metric)</b>	215.00 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	pack
<b>Package Quantity (Imperial)</b>	5000
<b>Package Quantity (Metric)</b>	5000
<b>Carton Quantity</b>	5000 Pieces
<b>Labels per Column</b>	12
<b>Labels per Row</b>	8
<b>Labels per Sheet</b>	96
<b>Sheets per Pack</b>	53
<b>Weight (Metric)</b>	0.66 kg

## Material and Specifications

---

<b>Material</b>	Type 105, Polyester (PET), white (WH)
<b>Material Shortcut</b>	105
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +300°F (-40°C to +149°C)
<b>ROHS compliant (Article 4 - 1)</b>	Yes