

## TAG51T3-100B

Article Number: 596-00014

Thermal Transfer Self-Laminating Label, 1.0" X .35" X .75", 3 Across, Vinyl, White, 10000/RL



Download spec sheet

### Base Data

<b>Local Order Number</b>	TAG51T3-100B
<b>Type</b>	TAG51T3
<b>Color</b>	White (WH)
<b>Features and Benefits</b>	<ul style="list-style-type: none"><li>• HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy.</li><li>• Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.</li><li>• Labels are UL recognized for indoor and outdoor use to expand application options.</li><li>• HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.</li></ul>
<b>Color Marking Field</b>	White (WH)
<b>Product Description</b>	HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.
<b>For Wire Type</b>	2 Pair Fiber
<b>Short Description</b>	Thermal Transfer Self-Laminating Label, 1.0" X .35" X .75", 3 Across, Vinyl, White, 10000/RL

### Product Dimensions

<b>Length L (Imperial)</b>	0.75 "
<b>Length L (Metric)</b>	19.05 mm
<b>Width W (Imperial)</b>	1.0 "
<b>Width W (Metric)</b>	25.4 mm
<b>Height H (Imperial)</b>	0.75 "
<b>Height H (Metric)</b>	19.05 mm
<b>Height H2 (Imperial)</b>	0.75 "
<b>Height H2 (Metric)</b>	19.1 mm
<b>Height of printable area (metric)</b>	8.8 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.053 "
<b>Bundle Diameter Min. (Metric)</b>	1.35 mm
<b>Bundle Diameter Max. (Imperial)</b>	0.118 "
<b>Bundle Diameter Max. (Metric)</b>	3.0 mm
<b>Horizontal Repeat HR (metric)</b>	27.3 mm
<b>Horizontal Repeat HR (imperial)</b>	1.075 "
<b>Print Method</b>	Thermal Transfer

<b>Thickness T (Metric)</b>	25 µm
<b>Vertical Repeat VR (imperial)</b>	0.94 "
<b>Vertical Repeat VR (metric)</b>	23.7 mm
<b>Width of Liner WL (imperial)</b>	3.35 "
<b>Width of Liner WL (metric)</b>	85.09 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	reel
<b>Package Quantity (Imperial)</b>	10000
<b>Package Quantity (Metric)</b>	10000
<b>Carton Quantity</b>	10000
<b>Labels per Row</b>	3
<b>Weight (Metric)</b>	0.56 kg

## Material and Specifications

---

<b>Material</b>	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
<b>Material Shortcut</b>	100B
<b>Adhesive</b>	Acrylic
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>ROHS compliant (Article 4 - 1)</b>	Yes
<b>Certification/Specification</b>	UL-Recognized
<b>UL Listed (US and Canada)</b>	No
<b>UL Listed (US)</b>	No