

Specification Sheet

Part Number: TAG5L-105

Product Image

Article Number	594-05105
Type	TAG5L
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">•Laser printable self-laminating polyester has a smooth surface, allowing for the highest resolution and print contrast.•The material is 1.0 mil thick, allowing it to conform around wires and cable.•The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.•Lasertags are not affected by the high heat required in a laser printer.
Quantity Per	pack
Product Description	HellermannTyton's self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using HellermannTyton's thermal transfer printers, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification.
Short Description	Laser Print Label, Self-Laminating, .8" x .5" x 1.43", 56 Per Sheet, PET, White, 5000/pkg
Global Part Name	TAG5L-105-WH
Local Order Number 2	594-05105

Width W (Imperial)	0.8
Width W (Metric)	20.3
Bundle Diameter Min (Imperial)	0.149
Bundle Diameter Min (Metric)	3.80
Bundle Diameter Max (Imperial)	0.29
Bundle Diameter Max (Metric)	7.60
Thickness T (Metric)	35.0
Width of Liner (Metric)	215.00
Width of Liner (imperial)	8.5
Outside Diameter Max(Imperial)	0.29
Outside Diameter Min (metric)	3.8
Outside Diameter Min(Imperial)	0.15
Outside Diameter Max (metric)	7.60
Material	Type 105, Polyester (PET), white (WH)
Material Shortcut	105
Adhesive	Acrylic

Halogen free No

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Operating Temperature (Metric) -40°F to +300°F (-40°C to +149°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3919905060

Content Unit(BMEcat) pcs.

Labels per Column 7

Labels per Row 8

Weight (Metric) 0.521

Weight (Imperial) 1.14