

TAG72T1-795

Article Number: 596-72795

Thermal Transfer Label, 2.75" X 1.25", 1 Across, Polyester, Silver, 3000/RL



Download drawing



Download spec sheet

Base Data

Local Order Number TAG72T1-795

Type TAG72T1

Color Silver (SR)

- Features and Benefits**
- Thermal transfer labels are made with high performance materials for long term industrial applications.
 - Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model.
 - The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.

Product Description Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.

Short Description Thermal Transfer Label, 2.75" X 1.25", 1 Across, Polyester, Silver, 3000/RL

Product Dimensions

Width W (Imperial) 2.75 "

Width W (Metric) 69.85 mm

Height H (Imperial) 1.25 "

Height H (Metric) 31.75 mm

Horizontal Repeat HR (metric) 69.85 mm

Horizontal Repeat HR (imperial) 2.75 "

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 1.375 "

Vertical Repeat VR (metric) 34.93 mm

Width of Liner WL (imperial) 2.95 "

Width of Liner WL (metric) 74.95 mm

Logistics and Packaging

Quantity Per reel

Package Quantity (Imperial) 3000

Package Quantity (Metric) 3000

Carton Quantity 3000 Pieces

Labels per Row 1

Weight (Metric) 0.608 kg

Material and Specifications

| | |
|---------------------------------------|---------------------------------------|
| Material | Type 795, Polyester, silver matt (SR) |
| Material Shortcut | 795 |
| Adhesive | Acrylic |
| Adhesive Shortcut | Acrylic |
| Adhesive Operating Temperature | -40°F to +300°F (-40°C to +149°C) |
| Operating Temperature | -40°F to +300°F (-40°C to +149°C) |
| ROHS compliant (Article 4 - 1) | Yes |
| Certification/Specification | UL-Recognized |
| UL Recognized (US and Canada) | Yes |