HellermannTyton

TAG82T2-822	
,	Article Number: 596-82822
-	hermal Transfer Label, 1.5" X .25", 2 Across, Polyester, White, 10000/RL
HellermannTyton	RoHS
PDF Deveload drawing	ad anno a baat
Let Download drawing Download	ad spec sheet
Base Data	
Local Order Numbe	r TAG82T2-822
Тур	a TAG82T2
Colo	r White (WH)
Features and Benefit	
	 Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating th need to be dedicated to one printer model.
	• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
Product Description	
	cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The produc
	is supplied on rolls on a 3" cardboard core.
Short Description	n Thermal Transfer Label, 1.5" X.25", 2 Across, Polyester, White, 10000/RL
Product Dimensions	
Width W (Imperia) 1.50 "
Width W (Metric) 38.1 mm
Height H (Imperia) 0.25 "
Height H (Metric) 6.35 mm
Horizontal Repeat HR (imperial) 1.50 "
Horizontal Repeat HR (metric) 38.1 mm
Print Metho	d Thermal Transfer
Vertical Repeat VR (imperial) 0.30 "
Vertical Repeat VR (metric) 7.62 mm
Width of Liner WL (imperial) 3.20 "
Width of Liner WL (metric) 81.28 mm
Logistics and Packaging	
Quantity Pe	r reel
Gounary I C	

Quantity Per	reel
Package Quantity (Imperial)	10000
Package Quantity (Metric)	10000
Carton Quantity	1
Labels per Row	2

Material and Specifications

Material Shortcut	822
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
ROHS compliant (Article 4 - 1)	Yes
Certification/Specification	UL-Recognized
UL Recognized (US and Canada)	Yes

© HellermannTyton 2015