



GENERAL PRODUCT SPECIFICATION
 Phone 800-316-8877 Fax 978-368-1276
www.jamesmonroewire.com

Description: Three Conductor, 10 AWG,
 Tray Cable With Overall PVC Jacket

Date: 4/24/2012

JM Part Number: JM56746
Reference: TC1003/PP-8JM1

Components Three 10 AWG Insulated Conductors

Conductor: 10 AWG, 105/30 bare copper

Insulation: .021" nominal wall of PVC (See Color Code)

Nylon Jacket: .005" nominal wall of Clear Nylon .186"

Cable Construction

Cabling: Three conductors cabled together, with fillers as necessary

Binder: Tissue Tape

Jacket: .053" nominal wall of Gray PVC .510"

Print

E73202 3/C 10 AWG (UL) TC-ER 90C DRY 75C WET 600V SUN RES DIR BUR
 OIL RES I/II OR MTW "FLEXING" OR WTTC 1000V OR DP-1
 OR c(UL) CIC-TC PVC/N FT4 --- LL41103 CSA AWM I/II A/B
 90C 600V FT4 --- ROHS CE

Color Code

- 1. Black
- 2. White
- 3. Green

Requirements

Temperature: 90°C
Voltage: 600V
 1000V - WTTC

Approvals: UL Type TC-ER
 UL WTTC, MTW, DP-1
 C(UL) CIC-TC, FT4
 CSA AWM, FT4
 Meets or exceeds NFPA 1901

Written By:	rjc	4/24/2012	Rev. 0	Initial Issue
Revised By:	scs	8/14/2012	Rev. 1	Added NFPA note
Revised By:	rjc	10/16/2012	Rev. 2	Change jacket color from Black to Gray per customer request
Revised By:	scs	10/19/2012	Rev. 3	Added JM and Reference Numbers