



**Description:** Five 10 AWG Conductors  
 Overall PVC Jacket

**Date:** 2/11/2013

**JM Part Number:** JM55250

**Reference:** TBD

**Components** Five 10 AWG Conductors

Conductor: 10 AWG, 10/.0234 bare copper

Insulation: .021" nominal wall of PVC (see color code)

Jacket: .005" nominal wall of Clear Nylon .168"

**Overall Cable Construction**

Cabling: Five conductors cabled around core filler

Binder: Clear Mylar tape

Jacket: .063" nominal wall of Black PVC .577"

**Print**

**E73202 5/C 10 AWG 600V TYPE TC (UL) 90C DRY 75C WET SUN RES DIR BUR**  
**--- LL41103 CSA AWM I/II A/B 90C 600V FT1**

**Color Code**

- |                                  |                                   |
|----------------------------------|-----------------------------------|
| 1. Black and printed " 1 - ONE " | 4. Blue and printed " 4 - FOUR "  |
| 2. White and printed " 2 - TWO " | 5. Green and printed " 5 - FIVE " |
| 3. Red and printed " 3 - THREE " |                                   |

**Requirements**

Temperature: 90°C Dry/75°C Wet  
 Voltage: 600V

Approvals: UL Type TC  
 CSA AWM FT1

Written By:	rjc	2/11/2013	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				