



Description: Three Conductor, 12 AWG,
 Tray Cable With Overall PVC Jacket

Date: 10/19/2012

JM Part Number: JM56747

Reference: TC1203/PP-0JM1

Components Three 12 AWG Insulated Conductors

Conductor: 12 AWG, 65/30 bare copper

Insulation: .016" nominal wall of PVC (See Color Code)

Nylon Jacket: .005" nominal wall of Clear Nylon .138"

Cable Construction

Cabling: Three conductors cabled together, with fillers as necessary

Binder: Tissue Tape

Jacket: .053" nominal wall of Gray PVC .406"

Print

E73202 3/C 12 AWG (UL) TC-ER 90C DRY 75C WET 600V SUN RES DIR BUR
 OIL RES I/II OR MTW "FLEXING" OR WTTC 1000V OR DP-1
 OR c(UL) CIC-TC PVC/N FT4 --- LL41103 CSA AWM I/II A/B
 90C 600V FT4 --- ROHS CE

Color Code

1. Black 2. White 3. Green

Requirements

Temperature: 90°C
 Voltage: 600V
 1000V - WTTC

Approvals: UL Type TC-ER
 UL WTTC, MTW, DP-1
 C(UL) CIC-TC, FT4
 CSA AWM, FT4
 Meets or exceeds NFPA 1901

Written By:	scs	10/19/2012	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				