



GENERAL PRODUCT SPECIFICATION
 Phone 800-316-8877 Fax 978-368-1275
 www.jamesmonroewire.com

Description: Four 12 AWG Insulated Conductors
 Overall Foil Shield and PVC Jacket

Date: 8/12/2013

JM Part Number: JM56974
Reference: TC1204OFS-PP-0

Components Four 12 AWG Insulated Conductors

Conductor: 12 AWG, 7/0305 bare copper
 Insulation: .016" nominal wall of PVC (See Color Code)
 Jacket: .005" nominal wall of Clear Nylon .134"

Cable Construction

Cabling: Four conductors cabled together, FRPP fillers as necessary
 Drain Wire: 12 AWG, 7/0305 tinned copper
 Shield: Aluminum-Mylar tape, Aluminum side IN
 Jacket: .047" nominal wall of Black PVC .421"

Print

E73202 4/C 12 AWG SHIELDED (UL) TC-ER 90C DRY 75C WET 600V --- LL41103
 CSA AWM I/II A/B 90C 600V FT4

Color Code

1. Black 2. Red 3. Blue 4. Orange

Requirements

Temperature: 90°C Approvals: UL Type TC-ER
 Voltage: 600V CSA AWM FT4

Signed off by: *Debbie Jamieson*

Accepted for our PO# 121187 and 122341

Written By:	rjc	8/12/2013	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				