



Description: Five Conductor 12 AWG Cable,
 Overall PVC Jacket

Date: 6/19/2012

JM Part Number: JM55763

Reference: TC1205/PP-0-JM

Components Four 12 AWG Insulated Conductors

Conductor: 12 AWG, 19/.0185 bare copper

Insulation: .016" nominal wall of PVC (See Color Code)

Nylon Jacket: .005" nominal wall of Clear Nylon .132"

Cable Construction

Cabling: Five conductors cabled together, with fillers as necessary for roundness

Binder: Clear Mylar tape

Jacket: .047" nominal wall of Black PVC .453"

Print

E73202 5/C 12 AWG 600V TYPE TC (UL) 90C DRY 75C WET SUN RES DIR BUR ---
 LL41103 CSA AWM I/II A/B 90C 600V FT1

Color Code

1. Black and numerically printed "1 - ONE"
2. White and numerically printed "2 - TWO"
3. Red and numerically printed "3 - THREE"
4. Blue and numerically printed "4 - FOUR"
5. Green and numerically printed "5 - FIVE"

Requirements

Temperature: 90C
 Voltage: 600V

Approvals: UL Type TC
 CSA AWM, FT1
 Sunlight Resistant
 Direct Burial

Written By:	rjc	6/19/2012	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				