

**Description:** Six Conductor, 12 AWG, Tray Cable  
 Overall PVC Jacket

**Date:** 6/16/2014

**JM Part Number:** JM55272  
**Reference:** TBD

**Components** Six 12 AWG Insulated Conductors

Conductor: 12 AWG, 19/.0185 tinned copper

Insulation: .016" nominal wall of PVC (See Color Code)

Nylon Jacket: .005" nominal wall of Clear Nylon .132"

**Cable Construction**

Cabling: Six conductors twisted together, FRPP fillers as necessary

Binder: Clear Mylar tape

Jacket: .047" nominal wall of Black PVC .493"

**Print**

**E73202 6/C 12 AWG 600V TYPE TC (UL) 90C DRY 75C WET SUN RES  
 DIR BUR --- LL41103 CSA AWM I/II A/B 90C 600V FT1 --- ROHS**

**Color Code**

- 1. Black and printed: " 1 - ONE "
- 2. Red and printed: " 2 - TWO "
- 3. Blue and printed: " 3 - THREE "
- 4. Orange and printed: " 4 - FOUR "
- 5. Yellow and printed: " 5 - FIVE "
- 6. Brown and printed: " 6 - SIX "

**Requirements**

Temperature: 90C  
 Voltage: 600V

Approvals: UL Type TC  
 CSA AWM, FT1  
 Sunlight Resistant  
 Direct Burial  
 Material are RoHS Compliant (2011/65/EU)

Written By:	rjc	6/16/2014	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				