ALPHA WIRE COMPANY
CDC PRODUCT SPECIFICATION

Part Number: IN070317 | Issue: 2
Page 1 of 1 Pages | Issue Date: 4/23/2007

A. Construction — **Diameters**

1) Component 1 — 4 X 1 COND
   a) Conductor — 14 (41/30) AWG BC
   b) Insulation — 0.032" Wall, Nom. PVC
      (1) Color Code — Alpha Wire Color Code KX

Cond	Color	Cond	Color	Cond	Color
1	GREEN/YELLOW	3	BLACK#2		
2	BLACK#1	4	BLACK#3		

2) Cable Assembly — 4 Components
   a) Core Wrap — CM Tape, 25% Overlap, Min.
3) Shield: — A/M/A Foil Tape, 25% Overlap, Min.
   a) Drain Wire — 14 (41/30) AWG TC
   a) Braid — TC,70% Coverage, Min.
4) Jacket — 0.065" Wall, Nom., PVC — 0.495"
   a) Color — BLACK
5) Packaging — 1000FT PUTUP

B. Industry Approvals

1) UL — TC/ER
2) CSA — AWM I/II A/B FT4
3) MIL — NONE

C. Physical & Mechanical Properties

1) Temperature — 90 C

D. Electrical Properties

1) Voltage Rating — 600 V_{RMS}

E. Other

1) Requested Quantity — 7,500Ft.

Application Notes

They want a drain wire for easy termination CSA/TC-ER/CE/Rohs.

Revision 2:

1. Changed color code to Alpha KX.

Note: Requote of CDC4206 except with change in color code.

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS