ALPHA WIRE COMPANY **CUSTOMER PRODUCT SPECIFICATION**

Part Number: 669245 3 Issue:

Page 1 of 2 Pages **Issue Date:** 10/9/2007 **Effective Date:** 10/9/2007

A. Construction **Diameters**

1) Component 1 12 X 1 COND 14 (41/30) AWG BC Conductor

Insulation 0.016" Wall, Nom. PVC/ 0.005" Wall NYLON 0.116 ALPHA NUMERIC NUMBERS - 1-ONE ALTERNATING AND (1) Print

INVERTED

(2) Color Code Alpha Wire Color Code RW

Cond	Color	Cond	Color	Cond	Color
1	GREEN/YELLOW	5	RED#4	9	RED#8
2	RED#1	6	RED#5	10	RED#9
3	WHITE/RED	7	RED#6	11	RED#10
4	RED#3	8	RFD#7	12	RED#11

2) Cable Assembly 12 Components Cabled 1.8 Twists/foot (min) Twists:

REMAY Tape, 25% Overlap, Min. b) Core Wrap

Jacket 0.065" Wall, Nom., TPE 0.627+/- 0.029

Color(s) **BLACK** a)

Print ALPHA WIRE-* P/N 669245 12C 14 AWG (2.08mm2) b)

> THHN SERIES P (UL) TYPE TC-ER 90C 600V OIL RES I/II SUN RES OR TYPE PLTC 90C --- LLXXXXXX CSA AWM IA/B IIA/B 90C 600V FT4 **ROHS** (DATE CODE) (SEQ FOOTAGE)

* = Factory Code

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Industry Approvals

UL 1)

> 90°C / 600V a) Component 1 THHN 90°C / 600V **MTW**

> 90°C / 600V b) Overall TC

> > **EXPOSED RUN**

SUN RES

PLTC 90°C

OIL RES I/II

2) CSA International AWM-I-A/B-II-A/B 90°C / 600V

FT4

3) EU Directive 2002/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous

substances in electrical and electronic equipment.

California Proposition 65: The outer surface materials used in the manufacture of this part meet the

requirements of California Proposition 65.

5) CE: LVD 73/23/EEC Amendment 93/68/EEC

C. Physical & Mechanical Properties

1) Temperature Range -25 to 90°C

Bend Radius 10X Cable Diameter 2) 3) Pull Tension 386 Lbs, Maximum

Sunlight Resistance 4) Yes

D. Electrical Properties (For Engineering purposes only)

 $600 \ V_{RMS}$ 1) Voltage Rating

Capacitance 34 pf/ft @1 kHz, Nominal Conductor to Conductor 2)

3) Inductance 0.17 uH/ft. Nominal

4) Conductor DCR 2.6 Ω/1000ft @20°C, Nominal

E. Other

1) Packaging

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION

Part Number: 669245	Issue:	3
Page 2 of 2 Pages	Issue Date:	10/9/2007
	Effective Date:	10/9/2007

- a) Bulk(Made-to-order)
- 2) Notes:
 - a) Moved MTW from overall industry approval to component 1. GK.

This Design is custom, Made-To-Order & once accepted, the order is NON-CANCELLABLE & NON-RETURNABLE.

Accepted By:	Date:
Company:	Title:

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.