

For more Information  
please call

1-800-Belden1



### General Description:

16 AWG stranded (7x24) bare copper conductors, twisted pairs, XLPE insulation, overall Beldfoil® shield (100% coverage), drain wire, insulated green ground wire, ripcord, PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Conductors	# Pairs	AWG	Stranding	Conductor Material
1	1	16	7x24	BC - Bare Copper

Total Number of Conductors: 3

#### Ground Wire

Ground Wire (Y/N): Y

Ground Wire AWG: 16

Ground Wire Stranding: 7x24

Ground Wire Conductor Material: BC - Bare Copper

Ground Wire Insulation Material: XLPE - Cross Linked Polyethylene

#### Insulation

Insulation Material:

Insulation Material
XLPE - Cross Linked Polyethylene

#### Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
18	7x26	TC - Tinned Copper

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.048

Outer Jacket Ripcord: Yes

#### Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	Black & White
2	Green

Overall Nominal Diameter: 0.390 in.

#### Pair

Pair Color Code Chart:

Number	Color
1	Black & White

### Mechanical Characteristics (Overall)

Wet Temperature Range: -30°C To +90°C

Dry Temperature Range: -30°C To +90°C

Bulk Cable Weight: 78 lbs/1000 ft.

Max. Recommended Pulling Tension: 130 lbs.

Min. Bend Radius/Minor Axis: 3.900 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC(UL) Specification:	TC-ER, UL 1277
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	08/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
Other Specification:	ICEA S-73-532, S-66-524

### Flame Test

UL Flame Test:	UL1685 UL Loading
C(UL) Flame Test:	FT4
IEEE Flame Test:	1202/383
ICEA Flame Test:	T-29-520

### Suitability

Suitability - Burial:	Yes
Sunlight Resistance:	Yes

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

61.2

### Nom. Mutual Capacitance:

Capacitance (pF/ft)

34

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

3.67

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

4.99

### Max. Operating Voltage - UL:

Voltage

600 V RMS (NEC Type TC)

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
3090CE 0101000	1,000 FT	81.000 LB	BLACK	C	1PR16 + GRN GRD TC-ER 600V
3090CE 0105000	5,000 FT	450.000 LB	BLACK	C Z	1PR16 + GRN GRD TC-ER 600V

### Notes:

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1    Revision Date: 05-14-2007

© 2015 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification.



## 3090CE Multi-Conductor - 600V Tray Cable

Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.