

Description: Twelve Conductor, 16 AWG,
 Tray Cable With Overall PVC Jacket

Date: 5/15/2013

JM Part Number: JM56914

Reference: TBD

Components

Twelve 16 AWG Singles

Conductor: 16 AWG, 26/30 bare copper

Insulation: .016" nominal wall of PVC (See Color Code)

Nylon Jacket: .005" nominal wall of Clear Nylon .100"

Cable Construction

Cabling: Twelve conductors cabled together, with fillers as necessary

Binder: Fleece tape

Jacket: .050" nominal wall of Black PVC .519"

Print

**E73202 12/C 16 AWG (UL) TC-ER 90C DRY 75C WET 600V SUN RES DIR BUR OIL RES II
 OR MTW OR C(UL) CIC-TC PVC/N FT4 --- LL41103 CSA AWM I/II A/B 90C 600V FT4**

Color Code

- | | |
|-----------|------------------|
| 1. Black | 7. White/Black |
| 2. White | 8. Red/Black |
| 3. Red | 9. Green/Black |
| 4. Green | 10. Orange/Black |
| 5. Orange | 11. Blue/Black |
| 6. Blue | 12. Black/White |

Requirements

Temperature: 90°C
 Voltage: 600V

Approvals: UL Type TC-ER
 UL Type MTW
 C(UL) CIC-TC, FT4
 CSA AWM, FT4
 Sunlight Resistant
 Direct Burial
 Oil Resistant II

Written By:	rjc	5/15/2013	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				