

Specification Sheet

Lake Cable Part #: V182S/18DR-QR

Description: 18 AWG 2 conductor 7 strand bare copper with polyvinylchloride and nylon insulation, an

aluminum/mylar shield with a stranded tinned copper drain wire with an overall PVC jacket 600V control tray cable, PLTC, NPLF & FPL, approved for use in SUN RES DIR BUR OIL RES I 90°C

applications.

1. Conductor

1.1. AWG Size & Stranding: 18 AWG, 7 Strands Class B 1.2. Material: Annealed Bare Copper

1.3. Conductor Count: 2 Conductors

2. Insulation

2.1. Material: Polyvinylchloride & Nylon
2.2. Wall Thickness: 0.015" PVC & 0.005" Nylon
2.3. Color Code: Method 1, Table E-2

3. Assembly

3.1. Lay Length: 2.75" LHL 3.2. Fillers: N/A 3.3. Binder: N/A

3.4. Shield: Aluminum/Mylar Tape - 100% coverage 3.5. Drain Wire: 18 AWG, 7 Strand Tinned Copper

4. Jacket

4.1. Material: Polyvinylchloride

4.2. Wall Thickness: 0.045"
 4.3. Diameter: 0.263"
 4.4. Color: Black
 4.5. Ripcord: Yes
 4.6. Cold Bend Rating: -40°C
 4.7. Weight: 42 lbs./Mft.

5. Markings

5.1. Type: Cable shall be permanently identified via surface inkjet print

5.2. Legend: LAKE CABLE E208309 18AWG 2C SHIELDED (UL) TC-ER 600V PLTC NPLF FPL

PVC/NYLON 600V 90'C DRY/WET PVC JACKET SUN RES DIR BUR OIL RES I FT4

"ROHS" MADE IN USA

5.3. Footage Markers: Yes

6. Standards

- 6.1. Refer to NEC (NFPA 70) article 336 for installation guidelines
- 6.2. Cable is suitable for use in Class I Division II hazardous locations
- 6.3. UL listed as Type TC-ER per UL Standard 1277 for tray cables and Quad Rated TC, PLTC, NPLF & FPL
- 6.4. UL approved for Direct Burial, Sunlight and Oil I Resistant applications
- 6.5. Cable meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements
- 6.6. Meets ICEA S-73-532, where applicable
- 6.7. All materials used in the manufacture of this cable are RoHS compliant
- 6.8. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION