



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 60355
DESCRIPTION: 18/3 COMPACT 600 TRAY CABLE ALASKA AUTO/MARINE
CONSTRUCTION: This cable consists of three bare copper insulated conductors cabled with a reinforced mylar wrap and an oil and sunlight resistant overall jacket.
APPROVALS: UL Standard 1277, NEC Article 336.
APPLICATION: 600 Volt Power and Control Tray Cable

Construction Parameters:

Conductor	18 AWG Bare Copper
Stranding	16/30
Insulation Material	PVC/Nylon
Insulation Thickness	0.021" Nom.
Insulated Conductor Diameter	0.088" Nom.
Number of Conductors	3
Lay Length	2.00" Nom.
Filler Type	Dry Jute
Separator/Wrap	Reinforced Mylar
Jacket Material	TPE
Jacket Thickness	0.050" Nom.
Overall Cable Diameter	0.305" Nom.
Approximate Cable Weight	46.5 Lbs/1M' Nom.
Flame Rating	UL 1581 Vertical Tray Flame Test

Electrical Properties:

Temperature Rating	-40°C to 90°C
Operating Voltage	300 V RMS Max.
DC Resistance per Conductor @ 20°C	6.49 Ohms/1M' Nom.

Insulation Colors	Blk Red White
Jacket Color	Black
Legend (White Surface Ink Print)	CCI 18 AWG 3/C COMPACT 600V (UL) TYPE TC 90C OIL RES I SUNLIGHT RESISTANT

This product complies with European Directive 2002/95/EC (RoHS)

The customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____ Date Signed _____

Customer Approval _____

Specification Issue Date: August 28, 2012