

CABLE AND HARNESS

Makers of Thrifty-Pull™, custom-bundled, multi-conductor cables

THRIFTY-PULL SPIRAL CONFIGURATION BUILDING WIRE CABLE ASSEMBLES WITH OVERALL TRAY RATED PVC JACKET

CONSTRUCTION DETAILS: Conductors as listed below are cabled together in a spiral configuration assembly with a left hand lay. Lay length determined per UL Spec 1277. Spiral assemblies are bound with a waxed nylon binder. Each individual conductor is labeled every 1.5" for identification. A PVC Tray Rated jacket is applied over the core. Assemblies are UL labeled and shipped on pull-length reels. Cable with 16 awg or 18 awg will not be direct burial rated.

CABLE COMPONENTS:

CABLE #1

Footage:	1 x 1,000'
Conductors:	48 conductors #18 AWG TFFN Stranded 600V 1 conductor black #1 1 conductor white #2 1 conductor green #3 1 conductor orange #4 43 conductors red #5-48
Jacket:	Black PVC tray rated jacket
OD:	.87"
Weight:	approx. 580#'s per reel

Thrifty-Pull cable assemblies are U.L. listed.

44 Hull Street, Suite 1—Randolph, VT 05060
P.O. Box 408 – Randolph, VT 05060
TOLL FREE: 800-346-6211 • Fax: 802-728-6784

