

## 29511 Composite - 1000V UL Flexible Motor Supply Cable



For more Information  
please call

1-800-Belden1



### Description:

1 pr.(Signal)-16 AWG stranded (26x30) TC cond., XLPE insul., Beldfoil® shield (100% c), drain; 3 cond.(VFD) plus 1 ground wire-14 AWG stranded (41x30) TC cond., XLPE insul., Duofoil® and TC braid Shield (100% a85% c), drain, PVC jacket.

### Usage (Overall)

**Suitable Applications:** AC Motor Drive, VFD, Variable Frequency Drive

### Twisted Pair

#### Physical Characteristics

##### Conductor

###### AWG:

# Pairs	AWG	Stranding	Conductor Material
1	16	26x30	TC - Tinned Copper

##### Insulation

###### Insulation Material:

Insulation Material	Wall Thickness (mm)
XLPE - Cross Linked Polyethylene	0.762

###### Twisted Pair Color Code Chart:

Number	Color
1	Black and White

##### Inner Shield

###### Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

###### Inner Shield Drain Wire AWG:

AWG	Stranding	Conductor Material
18	19x30	TC - Tinned Copper

#### Electrical Characteristics

##### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
111.554

##### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
13.124

##### Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/km)
16.372

### Multi Conductor

#### Physical Characteristics

##### Conductor

###### AWG:

# Conductors	AWG	Stranding	Conductor Material
--------------	-----	-----------	--------------------

## 29511 Composite - 1000V UL Flexible Motor Supply Cable

3	14	41x30	TC - Tinned Copper
---	----	-------	--------------------

### Ground Wire

Ground Wire (Y/N): Yes

#### Ground Wire Material:

AWG	Stranding	Conductor Material	Insulation Material
14	41x30	TC - Tinned Copper	PVC - Polyvinyl Chloride

### Insulation

#### Insulation Material:

Insulation Material	Wall Thickness (mm)
XLPE - Cross Linked Polyethylene	1.143

#### Insulation Color Code Chart:

Number	Color
1	Black #1
2	Black #2
3	Black #3
4	Green/Yellow

### Individual Shield

#### Outer Shield

#### Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100.000
2		Braid	TC - Tinned Copper	85.000

#### Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
14	41x30	TC - Tinned Copper

### Electrical Characteristics

#### Nom. Inductance:

Inductance (µH/m)
0.699

#### Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
137.802

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
75.463

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
8.268

### Physical Characteristics (Overall)

#### Conductor

#### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	1.905

Outer Jacket Ripcord: Yes

#### Overall Cable

Overall Nominal Diameter: 20.828 mm

### Mechanical Characteristics (Overall)

Max. Recommended Pulling Tension: 1636.938 N

Min. Bend Radius (Install)/Minor Axis: 208.280 mm

## 29511 Composite - 1000V UL Flexible Motor Supply Cable

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

<b>NEC/(UL) Specification:</b>	RHW-2 Singles, TC-ER, XHHW-2
<b>NEC Articles:</b>	335 - ER
<b>CSA Specification:</b>	1000 V AWM I/II A/B
<b>EU CE Mark:</b>	Yes
<b>EU Directive 2000/53/EC (ELV):</b>	Yes
<b>EU Directive 2002/95/EC (RoHS):</b>	Yes
<b>EU RoHS Compliance Date (mm/dd/yyyy):</b>	09/21/2006
<b>EU Directive 2002/96/EC (WEEE):</b>	Yes
<b>EU Directive 2003/11/EC (BFR):</b>	Yes
<b>CA Prop 65 (CJ for Wire &amp; Cable):</b>	Yes
<b>MII Order #39 (China RoHS):</b>	Yes
<b>PMSHA Specification:</b>	P-07-KA070003
<b>Other Specification:</b>	1000V UL Flexible Motor Supply Cable

#### Flame Test

<b>UL Flame Test:</b>	UL1685 UL Loading
<b>CSA Flame Test:</b>	FT4
<b>IEEE Flame Test:</b>	1202, IEEE 383 Vertical Tray Flame Test (70,000 BTU)

#### Suitability

<b>Suitability - Indoor:</b>	Yes
<b>Suitability - Outdoor:</b>	Yes
<b>Suitability - Burial:</b>	Yes
<b>Sunlight Resistance:</b>	Yes

#### Plenum/Non-Plenum

<b>Plenum (Y/N):</b>	No
----------------------	----

### Electrical Characteristics (Overall)

#### Max. Operating Voltage - UL:

<b>Voltage</b>
1000 V RMS (Flexible Motor Supply Cable)

#### Max. Operating Voltage - Other:

<b>Voltage</b>
1000 V RMS (CSA AWM I/II A/B)

### Related Documents:

No related documents are available for this product

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
29511 010100	30 MT	30.618 KG	BLACK	C	COMPOSITE CABLE SH PVC
29511 0101000	305 MT	154.222 KG	BLACK	C	COMPOSITE CABLE SH PVC
29511 010500	152 MT	80.513 KG	BLACK	C	COMPOSITE CABLE SH PVC
29511 0105000	1,524 MT	709.875 KG	BLACK	C	COMPOSITE CABLE SH PVC

#### Notes:

C = CRATE REEL PUT-UP.

## 29511 Composite - 1000V UL Flexible Motor Supply Cable

Revision Number: 0    Revision Date: 10-19-2011

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.