


# TCGT UL/CSA Approved 250° C., 600 Volt



- A. Center conductor - stranded, nickel plated copper
- B. Insulation - PTFE tape, ceramic tape
- C. Jacket - fiberglass saturated with high temperature finish

**Applications**

Internal wiring of appliances and domestic, commercial and industrial ovens. Also used in cooking, curing and drying equipment. Ideal for high temperature, harsh environments found in heaters, furnaces, ovens, and kilns.

**Listings**

250° C. 600 volt: UL 5288; CSA: Class 1, Group A/B

Catalog Number	Size (AWG)	Stranding (No./AWG)	Insulation Thickness (mils)	Overall Diameter (inches)	Weight (lbs/1000 ft)	Part Number	
						U.S.	Canada
TCGT600-20	20	10/30	30	.107	10	J1551	J102
TCGT600-18	18	16/30	30	.115	13	J1550	J103
TCGT600-16	16	26/30	30	.129	18	J1549	J104
TCGT600-14	14	41/30	30	.140	22	J1548	J105
TCGT600-12	12	65/30	30	.155	30	J1547	J106
TCGT600-10	10	105/30	30	.207	49	J1546	J107
TCGT600-8	8	133/29	30	.243	73	J1545	J108
TCGT600-6	6	133/27	43	.305	118	-	J109
TCGT600-4	4	133/25	43	.361	175	-	J110
TCGT600-2	2	133/23	43	.439	267	-	J111

*All figures referenced are nominal.*

