1. CONDUCTOR:

1.1 Size and Material: 16 26/30 AWG nickel-plated copper wire.

1.2 O.D.: .0565" nom.

2. INSULATION:

2.1 Spiral-wrapped PTFE skived tape.

2.2 Spiral-wrapped ceramic tape.

2.3 Braided fiberglass yarn impregnated with a silicone saturant to minimize fraying.

2.4 Marking on the insulation: as per UL and CSA Standards.

2.5 O.D.: .1255" nom.

2.6 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:

3.1 Voltage rating: 600 VAC R.M.S.

3.2 Temperature rating: 250°C


4. REFERENCES:

4.1 UL Subject 758 (AWM), Style 5288.

4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: .			
Date:			



UNCONTROLLED DOCUMENT
A later revision of this specification may exist.

Date: October 15, 2009

ied: Pantslär

October 15, 2009

1 of 1

Scale:



1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3
Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourltd.com

Description:

Code Ident. No:

57104

TCGS600 1626/30N-T

Specification No.: Rev.

Wire & Cable Specification - HBR.04.86.D

