

**1. CONDUCTOR:**

- 1.1 Size and Material: 18 19/30 AWG nickel-plated copper wire.
- 1.2 O.D.: .047" nom.

**2. INSULATION:**

- 2.1 Spiral-wrapped PTFE skived tape.
- 2.2 One layer of spiral-served fibreglass yarn.
- 2.3 Braided fibreglass yarn impregnated with a saturant to minimize fraying.
- 2.4 Marking on the braid: as per UL and CSA Standards.
- 2.5 O.D.: .094" nom.
- 2.6 Color: tan.

**3. PERFORMANCE:**

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 250°C




**4. REFERENCE:**

- 4.1 UL Subject 758 (AWM), Style 5256.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I, Group A/B.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.								 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: <i>Pierre Garand</i> Date: April 20, 2006		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3                  Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com</p>					
1346									Verified: <i>David Lott</i> Date: April 20, 2006		Description: <b>TG600 1819/30N-T (.094" nom.)</b>					
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.									 <p>A member of The Marmon Group of companies</p>		Size: <b>A</b>	Scale: ---	Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>F02086-T</b>	Rev. <b>A</b>