



<b>18 AWG (1.02MM) Solid</b>	1	.037	(0.94)	.234	(5.9)	1.4	(36)	34	(15)	34	(51)
	4	.053	(1.35)	.424	(10.8)	2.5	(65)	112	(51)	105	(156)
	8	.053	(1.35)	.525	(13.3)	3.2	(80)	216	(98)	174	(259)
	12	.064	(1.63)	.634	(16.1)	3.8	(97)	320	(145)	255	(379)
	16	.064	(1.63)	.706	(17.9)	4.2	(108)	424	(193)	321	(478)
	20	.064	(1.63)	.734	(18.6)	4.4	(112)	528	(240)	383	(569)
	24	.064	(1.63)	.828	(21.0)	5.0	(126)	632	(287)	453	(674)
36	.074	(1.88)	.956	(24.3)	5.7	(146)	944	(429)	656	(976)	
<b>20 AWG (0.81MM) Solid</b>	1	.037	(0.94)	.218	(5.5)	1.3	(33)	21	(10)	28	(42)
	4	.042	(1.07)	.369	(9.4)	2.2	(56)	72	(33)	77	(115)
	8	.053	(1.35)	.480	(12.2)	2.9	(73)	136	(62)	136	(202)
	12	.053	(1.35)	.557	(14.1)	3.3	(85)	200	(91)	188	(280)
	16	.064	(1.63)	.643	(16.3)	3.9	(98)	264	(120)	242	(360)
	20	.064	(1.63)	.669	(17.0)	4.0	(102)	328	(149)	292	(434)
	24	.064	(1.63)	.752	(19.1)	4.5	(115)	392	(178)	343	(510)
36	.064	(1.63)	.848	(21.5)	5.1	(129)	584	(265)	479	(713)	

The products referenced above represent the most popular constructions. Other constructions can be manufactured to meet individual specification and application requirements. Contact factory for additional information.

**Table 1**

Initial Calibration Tolerances Per ASTM E230 and ANSI MC96.1

<u>Thermocouple Type</u>	<u>Temperature Range F(C)</u>	<u>Grade Designation</u>	<u>Tolerance-Reference Junction 32F (0C)</u>		
			<u>Standard Grade Limits F(C)</u>	<u>Grade Designation</u>	<u>Special Grade Limits F(C)</u>
<u>Extension Wire</u>					
TX	32 (0) to 212 (100)	TX	±1.8 (1)	TTX	±0.9 (0.5)
JX	32 (0) to 400 (200)	JX	±4 (2.2)	JJX	±2 (1.1)
EX	32 (0) to 400 (200)	EX	±3.1 (1.7)	EEX	±1.8 (1)
KX or NX	32 (0) to 400 (200)	KX or NX	±4 (2.2)	KKX or NNX	±2 (1.1)
<u>Compensating Extension Wire</u>					
RX or SX	32 (0) to 400 (200)	RX or SX	±9 (5)		

**Electrical Characteristics**

Insulation passes 3000 V ac spark test per UL Subject 13.  
Completed cable passes a dielectric test of 2500 V dc for 10 seconds, conductor to conductor and conductor to shield, per UL Subject 13.



**TE Wire & Cable LLC**

107 North Fifth Street  
Saddle Brook, NJ 07663-6167  
Toll Free: 888-483-9473  
Tel: 201-845-9400  
Fax: 201-291-1190



A Marmon Wire & Cable/Berkshire Hathaway Company