


**AWC101 Telecommunications Interconnect Cable
Multi-conductor Unshielded - Flat (oval)**




Flat (oval) multi-conductor unshielded modular type telecommunications interconnect cable consisting of stranded bare or tinned copper or tinsel conductors with thermoplastic insulation in a PVC (Polyvinyl chloride) jacket.

AWC Standard Number	Number of Conductors	AWG & Stranding	Insulation Thickness (Nom. In.)	Jacket Thickness (Nom. In.)	Outside Dimension (Nom. In.)
AWC10125	2	24-7/32-TSC	0.007	0.028	0.096 X 0.150
AWC10150	2	26-7/34-BSC	0.009	0.028	0.096 X 0.150
AWC10126	2	26-7/34-TSC	0.009	0.028	0.096 X 0.150
AWC10101	2	28-7/36-BSC	0.011	0.028	0.096 X 0.150
AWC10102	2	28-7/36-TSC	0.011	0.028	0.096 X 0.150
AWC10103	2	TINSEL	0.008	0.028	0.096 X 0.150

NOTE

Color Code: 1) Red, 2) Grn
 Available jacket colors: W = Silver Satin
 Available put-ups: 500, 1,000, 2,500, 5,000, 10,000 foot reels
 Ordering example: AWC10125-W-500
 Other color codes and/or jacket colors available upon request.
 UL Recognition labeling available upon request.

**AWC101 Telecommunications Interconnect Cable
Multi-conductor Unshielded - Flat (oval)**



Flat (oval) multi-conductor unshielded modular type telecommunications interconnect cable consisting of stranded bare or tinned copper or tinsel conductors with thermoplastic insulation in a PVC (Polyvinyl chloride) jacket.

AWC Standard Number	Number of Conductors	AWG & Stranding	Insulation Thickness (Nom. in.)	Jacket Thickness (Nom. in.)	Outside Dimension (Nom. in.)
AWC10104	2	28-7/36-BSC	0.011	0.028	0.096 X 0.150
AWC10105	2	28-7/36-TSC	0.011	0.028	0.096 X 0.150
AWC10106	2	TINSEL	0.008	0.028	0.096 X 0.150

NOTE

Color Code: 1) Gry, 2) Gry
 Available jacket colors: TA = Clear
 Available put-ups: 500, 1,000, 2,500, 5,000, 10,000 foot reels
 Ordering example: AWC10104-TA-500
 Other color codes and/or jacket colors available upon request.
 UL Recognition labeling available upon request.