




**AWC101 Telecommunications Interconnect Cable
Multi-conductor Unshielded - Flat (oval)**



Flat (oval) multi-conductor unshielded modular type telecommunications interconnect cable consisting of stranded bare or tinned copper or tinsel conductors with thermoplastic insulation in a PVC (Polyvinyl chloride) jacket.

AWC Standard Number	Number of Conductors	AWG & Stranding	Insulation Thickness (Nom. In.)	Jacket Thickness (Nom. In.)	Outside Dimension (Nom. In.)
AWC10127	4	24-7/32-TSC	0.007	0.020	0.090 X 0.190
AWC10151	4	26-7/34-BSC	0.009	0.020	0.090 X 0.190
AWC10128	4	26-7/34-TSC	0.009	0.020	0.090 X 0.190
AWC10107	4	28-7/36-BSC	0.011	0.020	0.090 X 0.190
AWC10108	4	28-7/36-TSC	0.011	0.020	0.090 X 0.190
AWC10109	4	TINSEL	0.008	0.020	0.090 X 0.190

NOTE

Color Code: 1) Blk, 2) Red, 3) Grn, 4) Yel

Available jacket colors: C = Ivory

W = Silver Satin


Available put-ups: 500, 1,000, 2,500, 5,000, 10,000 foot reels

Ordering example: AWC10127-C-500

Other color codes and/or jacket colors available upon request.

UL Recognition labeling available upon request.

**AWC101 Telecommunications Interconnect Cable
Multi-conductor Unshielded - Flat (oval)**



Flat (oval) multi-conductor unshielded modular type telecommunications interconnect cable consisting of stranded bare or tinned copper or tinsel conductors with thermoplastic insulation in a PVC (Polyvinyl chloride) jacket.

AWC Standard Number	Number of Conductors	AWG & Stranding	Insulation Thickness (Nom. in.)	Jacket Thickness (Nom. in.)	Outside Dimension (Nom. in.)
AWC10110	4	28-7/36-BSC	0.011	0.020	0.090 X 0.190
AWC10111	4	28-7/36-TSC	0.011	0.020	0.090 X 0.190
AWC10112	4	TINSEL	0.008	0.020	0.090 X 0.190

NOTE

Color Code: 1) Gry, 2) Gry, 3) Gry, 4) Gry

Available jacket colors: TA = Clear

Available put-ups: 500, 1,000, 2,500, 5,000, 10,000 foot reels

Ordering example: AWC10110-TA-500

Other color codes and/or jacket colors available upon request.

UL Recognition labeling available upon request.