


**AWC101 Telecommunications Interconnect Cable
Multi-conductor Unshielded - Flat (oval)**




Flat (oval) multi-conductor unshielded modular type telecommunications interconnect cable consisting of stranded bare or tinned copper or tinsel conductors with thermoplastic insulation in a PVC (Polyvinyl chloride) jacket.

AWC Standard Number	Number of Conductors	AWG & Stranding	Insulation Thickness (Nom. In.)	Jacket Thickness (Nom. In.)	Outside Dimension (Nom. In.)
AWC10129	6	24-7/32-TSC	0.007	0.024	0.090 X 0.270
AWC10152	6	26-7/34-BSC	0.009	0.024	0.090 X 0.270
AWC10130	6	26-7/34-TSC	0.009	0.024	0.090 X 0.270
AWC10113	6	28-7/36-BSC	0.011	0.024	0.090 X 0.270
AWC10114	6	28-7/36-TSC	0.011	0.024	0.090 X 0.270
AWC10115	6	TINSEL	0.008	0.024	0.090 X 0.270

NOTE

Color Code: 1) Wht, 2) Blk, 3) Red, 4) Grn, 5) Yel, 6) Blu
 Available jacket colors: W = Silver Satin
 Available put-ups: 500, 1,000, 2,500, 5,000, 10,000 foot reels
 Ordering example: AWC10129-W-500
 Other color codes and/or jacket colors available upon request.
 UL Recognition labeling available upon request.

**AWC101 Telecommunications Interconnect Cable
Multi-conductor Unshielded - Flat (oval)**



Flat (oval) multi-conductor unshielded modular type telecommunications interconnect cable consisting of stranded bare or tinned copper or tinsel conductors with thermoplastic insulation in a PVC (Polyvinyl chloride) jacket.

AWC Standard Number	Number of Conductors	AWG & Stranding	Insulation Thickness (Nom. in.)	Jacket Thickness (Nom. in.)	Outside Dimension (Nom. in.)
AWC10116	6	28-7/36-BSC	0.011	0.024	0.090 X 0.270
AWC10117	6	28-7/36-TSC	0.011	0.024	0.090 X 0.270
AWC10118	6	TINSEL	0.008	0.024	0.090 X 0.270

NOTE

Color Code: 1) Gry, 2) Gry, 3) Gry, 4) Gry, 5) Gry, 6) Gry
 Available jacket colors: TA = Clear
 Available put-ups: 500, 1,000, 2,500, 5,000, 10,000 foot reels
 Ordering example: AWC10116-TA-500
 Other color codes and/or jacket colors available upon request.
 UL Recognition labeling available upon request.