




**AWC101 Telecommunications Interconnect Cable
Multi-conductor Unshielded - Flat (oval)**



Flat (oval) multi-conductor unshielded modular type telecommunications interconnect cable consisting of stranded bare or tinned copper or tinsel conductors with thermoplastic insulation in a PVC (Polyvinyl chloride) jacket.

| AWC Standard Number | Number of Conductors | AWG & Stranding | Insulation Thickness (Nom. In.) | Jacket Thickness (Nom. In.) | Outside Dimension (Nom. In.) |
|---------------------|----------------------|-----------------|---------------------------------|-----------------------------|------------------------------|
| AWC10131 | 8 | 24-7/32-TSC | 0.007 | 0.024 | 0.090 X 0.350 |
| AWC10154 | 8 | 26-7/34-BSC | 0.009 | 0.024 | 0.090 X 0.350 |
| AWC10132 | 8 | 26-7/34-TSC | 0.009 | 0.024 | 0.090 X 0.350 |
| AWC10119 | 8 | 28-7/36-BSC | 0.011 | 0.024 | 0.090 X 0.350 |
| AWC10120 | 8 | 28-7/36-TSC | 0.011 | 0.024 | 0.090 X 0.350 |
| AWC10121 | 8 | TINSEL | 0.008 | 0.024 | 0.090 X 0.350 |

NOTE

Color Code: 1) Gry, 2) Org, 3) Blk, 4) Red, 5) Grn, 6) Yel, 7) Blu, 8) Brn

Available jacket colors: W = Silver Satin

Available put-ups: 500, 1,000, 2,500, 5,000, 10,000 foot reels

Ordering example: AWC10131-W-500

This color code is commonly used with 8 position UNKEYED modular plugs.

Other color codes and/or jacket colors available upon request.

UL Recognition labeling available upon request.

**AWC101 Telecommunications Interconnect Cable
Multi-conductor Unshielded - Flat (oval)**



Flat (oval) multi-conductor unshielded modular type telecommunications interconnect cable consisting of stranded bare or tinned copper or tinsel conductors with thermoplastic insulation in a PVC (Polyvinyl chloride) jacket.

| AWC Standard Number | Number of Conductors | AWG & Stranding | Insulation Thickness (Nom. In.) | Jacket Thickness (Nom. In.) | Outside Dimension (Nom. In.) |
|---------------------|----------------------|-----------------|---------------------------------|-----------------------------|------------------------------|
| AWC10133 | 8 | 24-7/32-TSC | 0.007 | 0.024 | 0.090 X 0.350 |
| AWC10155 | 8 | 26-7/34-BSC | 0.009 | 0.024 | 0.090 X 0.350 |
| AWC10134 | 8 | 26-7/34-TSC | 0.009 | 0.024 | 0.090 X 0.350 |
| AWC10122 | 8 | 28-7/36-BSC | 0.011 | 0.024 | 0.090 X 0.350 |
| AWC10123 | 8 | 28-7/36-TSC | 0.011 | 0.024 | 0.090 X 0.350 |
| AWC10124 | 8 | TINSEL | 0.008 | 0.024 | 0.090 X 0.350 |

NOTE

Color Code: 1) Blu, 2) Org, 3) Blk, 4) Red, 5) Grn, 6) Yel, 7) Brn, 8) Gry

Available jacket colors: W = Silver Satin

Available put-ups: 500, 1,000, 2,500, 5,000, 10,000 foot reels

Ordering example: AWC10133-W-500

This color code is commonly used with 8 position KEYED modular plugs.

Other color codes and/or jacket colors available upon request.

UL Recognition labeling available upon request.



Customer Service Phone # 01-800-237-4542 Fax. # 802-419-3751

Re: Certificate of Environmental Compliance RoHS for IEWC Corp.

Part number: AWC10132-W-1000

Dear, Patti Starich
RoHS Coordinator

I certify that I am authorized to declare this Material Declaration on my behalf of my company; that the information contained herein is true and accurate to the best of my knowledge and belief. I further certify that any changes to the reported concentration levels of restricted substances require a re-submission of the Material Declaration to IEWC Corp.

Based on the information collected from our sub-suppliers raw materials I declare that all the part numbers do meet the RoHS initiative from the European Community Parliament in terms of Lead, Cadmium, Hexavalente Chrome, Mercury, PBDE and PBB content into the copper conductor, connectors and plastic jackets. All of the restricted substances meet the requirements.

If you need further information, please feel free to contact me.

Sincerely

Roberto Ruiz
Quality Control Engineer
Adirondack Wire & Cable
Div. Whitney Blake Co.
Monterrey, N.L.
August 14, 2012