

# Drop Wire

# Spec. 4295

## BELL SYSTEM TYPE F DROP AND RUS (REA) PE-7



CATALOG NUMBER	PAIRS AWG	O.D. (INCHES)	WEIGHT (LBS/MFT)	STANDARD LENGTH (FT)
7021421	1/18 <sup>1/2</sup>	0.130 x 0.255	24	1000 CL
7021496	1/18 <sup>1/2</sup>	0.130 x 0.255	24	1000 PP
7021512	1/18 <sup>1/2</sup>	0.130 x 0.255	24	1000 CL/CTN
2091004	1/18 <sup>1/2</sup>	0.130 x 0.255	24	2500 RL

Data subject to change without notice. Contact your Customer Service Representative for latest information.

**Product Construction:****Conductors:**

- 18<sup>1/2</sup> AWG solid 30% conductivity extra high strength copper-covered steel

**Sheath:**

- Black, flame-, weather- and abrasion-resistant PVC compound extruded over two conductors in a parallel configuration

**Polarity Identification:**

- Polarity ridge on one leg of the web located at 45° above the major axis of the wire cross-section

**Application(s):**

- Self-supporting one pair parallel conductor drop wire intended for aerial service connection to the subscriber

**Compliance:**

- Telecordia (Bellcore) Specification TR-NWT-000121
- Rural Utilities Service (RUS) Bulletin 1753 F-204 (REA PE-7)
- ANSI/CEA S-89-648-1993

**Packaging:**

- Available in Pull-Pac™ cartons (PP), coils in cartons (CL/CTN) and reels (RL)

