

AUTOMOTIVE BATTERY CABLE

AUTOMOTIVE

Crosslink polyethylene (XPLE) insulated wire manufactured to SAE J1127 standards to meet the following specifications:

FORD: M1L 92A
DELPHI PACKARD: ESM-3024

SGX Bare Copper 125°C

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
SGX-6-37-B	82.00	37/0266	.065	25M*
SGX-6-49-B	79.00	49/0232	.065	25M*
SGX-4-61-B	118.00	61/0249	.065	25M*
SGX-4-133-B	122.00	133/0177	.065	25M*
SGX-4-1000	115.00	133/0170	.065	25M
SGX-4-1001	122.00	61/0249	.065	25M
SGX-4-1002	122.00	133/0170	.065	25M
SGX-4-1003	122.00	61/0249	.065	25M
SGX-4-1004	118.00	61/0249	.065	25M
SGX-2-133-B	192.80	133/0217	.065	25M
SGX-2-1000	192.80	133/0217	.065	25M
SGX-1-133-B	246.70	133/0242	.065	25M

SGX Tinned Copper 125°C

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
SGX-6-266-T	83.73	266/0098	.065	25M
SGX-4-133-T	130.61	133/0177	.065	25M

Minimum order requirement reflects quantity per color, per release.
* 15,000 foot minimum on red, white, or black

800-776-9223 (Ohio) 800-684-7823 (Texas)