



X	NOM. O.D.	NOM. I.D.	NOM. WALL	ToI. O.D.
1	0.040"	0.036"	0.002"	± 0.002
2	0.088"	0.082"	0.003"	± 0.003"
3	0.098"	0.092"	0.003"	± 0.003"
4	0.118"	0.114"	0.002"	± 0.002"
5	0.131"	0.126"	0.0025"	± 0.002"
6	0.056"	0.053"	0.0015"	± 0.002"
7	0.186"	0.180"	0.003"	± 0.002"
8				
9				
10				
11				
12				
13				
14				
15				

NOTE: ORDER POLYIMIDE TUBING IN 36" ± 1" LENGTHS.
 MATERIAL: SPIRAL WOUND POLYIMIDE TUBING
 TEMP. RANGE: -80°C TO 300°C CONTINUOUS

REV. D - ADD "-7"
 REV. C - ADD "-6"
 REV. B - ADD "-5"
 REV. A - ADD "-4"

BetaTHERM CORP.
 910 TURNPIKE RD., SHREWSBURY, MA 01545

THE INFORMATION CONTAINED IN THIS DOCUMENT IS CONFIDENTIAL AND MUST NOT BE DISCLOSED EXCEPT AS AUTHORIZED IN WRITING BY BETATHERM CORPORATION.

TOL.		REVISIONS		RAW MATERIAL-POLYIMIDE			
REV.	DATE	BY					
A	09/26/2000	KC					
B	02/02/2001	KC		DRAWN BY	D.S.	SCALE	NONE
C	05/16/2002	KC		DATE	3/11/97		
D				APPROVED			

TPO-046-(X)