



	NOM. O.D.	NOM. I.D.	NOM. WALL	Tol. O.D.
X				
1	0.040"	0.036"	0.002"	± 0.002
2	0.088"	0.082"	0.003"	± 0.003"
3	0.098"	0.092"	0.003"	± 0.003"
4	0.118"	0.114"	0.002"	± 0.002"
5	0.131"	0.126"	0.0025"	± 0.002"
6	0.056"	0.053"	0.0015"	± 0.002"
7	0.185"	0.180"	0.003"	± 0.002"
8				
9				
10				
11				
12				
13				
14				
15				

NOTE: ORDER POLYIMIDE TUBING IN 36" ± 1" LENGTHS.

MATERIAL: SPIRAL WOUND POLYIMIDE TUBING

TEMP. RANGE: -80°C TO 300°C CONTINUOUS

REV. D - ADD "-7"

REV. C - ADD "-6"

REV. B - ADD "-5"

REV. A - ADD "-4"

BetaTHERM CORP.

910 TURNPIKE RD., SHREWSBURY, MA 01545

THE INFORMATION CONTAINED IN THIS DOCUMENT IS CONFIDENTIAL AND MUST NOT BE DISCLOSED EXCEPT AS AUTHORIZED IN WRITING BY BETA THERM CORPORATION.

TOL.	REV.	DATE	BY	RAW MATERIAL-POLYIMIDE			
DECIMAL	A						
	B	09/26/2000	KC				
FRACTIONAL	C	02/02/2001	KC	SCALE BY	D.S.	SCALE	NONE
	D	05/16/2002	KC	DATE		DATE	3/11/97
ANGULAR	E			TRACED		APPRO	
	F						TPO-046-(X)