



2850 E. SPRUCE ST • OILTARIO • (714) 91761  
(909) 923-8800 • 1(800) 233-2139 • FAX (909) 923-8865







December 4, 2006

F/N #9800

**CUSTOMER SPECIFICATION**

**#1/8,1/10,5/12 GAUGES**

**BEE FLEX TRAILER CABLE MEETS SAE AND ATA SPECIFICATIONS  
WITH  
TEMPERATURE RANGE FROM -55°C TO +85°C.**



**CONDUCTOR:** (#8) 168 X .010 ± .001 EACH STRAND  
SOFT ANNEALED BARE COPPER

(#10) 104 X .010  
± .001 ON EACH STRAND  
SOFT ANNEALED BARE COPPER

(#12) 65 X .010  
± .001 ON EACH STRAND  
SOFT ANNEALED BARE COPPER

**INSULATION:** (#8) .030 NOMINAL PVC INSULATION  
COLOR CODE: WHITE

(#10) .032 NOMINAL WALL OF PVC INSULATION  
COLOR CODE: RED

(#12) .032 NOMINAL WALL OF PVC INSULATION  
COLOR CODED BLACK, YELLOW, GREEN, BROWN,  
AND BLUE.

**CABLE ASSEMBLY:** SEVEN CONDUCTORS CABLE TOGETHER WITH FILLER  
(IF NECESSARY) AROUND #08 WHITE, #10 RED,  
#12 BLACK, #12 YEL, #12 GRN, #12 BRN, #12 BLUE.

**JACKET:** .070 NOMINAL WALL OF FLEXIBLE COMPOUND.  
PVC OD .680 ± .010

**WRITTEN BY:** Ariam R. Bera  
ARIAM R. BERA, PRESIDENT

**CUSTOMER APPROVAL** \_\_\_\_\_

Excellence Through Quality . . .